PRO-MAX SERIES ELECTRIC POLYCHAIN BELT DRIVE

Distributed By: R.J. Sayers Distributing, LLC 21020 Cambodia Ave Farmington, MN 55024 651-460-6101 / 800-456-9840 info@sayerswashsystems.com

*Picture shown may not represent exact model. Consult factory

B5535E3G403

5.5GPM@3500PSI

230V/3PH/34A **15HP**



HP5535 Pump

Standard Accessories

- Gun/wand assembly w/quick connects
- 50' high pressure hose w/quick connects
- Chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

Available Options

- Skid Mount Precede model with S/ Example: S/B5535E3G303
- Block Mounted K7 Unloader
- 3500 psi max
- Auto Start/Stop (230V)
- Auto Start/Stop w/time delay-consult factory
- 460V available consult factory

NOTE: Review specs for models with Auto Start/ Stop options as these units are custom made and NONCANCELABLE & NONRETURNABLE.

OMARATHON[®] EM3713T Motor

Standard Features

- Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- Lifetime frame warranty
- Easy access tip holder/gun holder/hose hanger on handle
- Epoxy powder coated finish
- 10,000 hour rated Gates polychain cogged belt (two year warranty)
- 50 mesh inlet water filter
- Adjustable pressure unloader
- Oversize pneumatic tires
- Dual spring cushioned shock absorbing feet
- 3/4" cold-rolled steel threaded axle
- Low speed pump and thermo-sensor (prevents overheating in bypass mode)
- TEFC Commercial/Industrial motors
- Mag Starter assembly, w/thermal overload, and startstop buttons in NEMA enclosure w/12 ' power cord (no plug)

NOTE: 8 GPM units set up for tank feed.