

Distributed By:
R.J. Sayers Distributing, ILC
21020 Cambodia Ave
Farmington, MN 55024
651-460-6101 / 800-456-9840
info@sayerswashsystems.com

PPS4042HGI

4GPM@4200PSI



TX1510G8UIA PUMP

Standard Accessories

- Gun/wand assembly
- ♦ 25' hose w/ couplers
- Chemical injector
- ♦ 3 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle NOTE: 2700-3300 PSI models include 22mm twist coupler socket hose ends; 4200 PSI models include 22mm twist socket x 3/8" QC plug hose ends.

Available Options

- Skid Mount precede model with S/, Example: S/PPS4042LAI.
- ◆ 50' Hose Upgrade -add -50 suffix to model, Example: PPS2533HAI-50

HONDA GX390 Engine

Standard Features

- Revolutionary aircraft grade aluminum frame with dual handles (no welds to fail)
- Lifetime frame warranty
- 50 mesh inlet filter
- Adjustable pressure unloader
- Low oil shutdown Kohler, LCT & GX models only
- Pneumatic tires
- Dual padded shock absorbing feet
- 3/4" cold-rolled steel axle
- Kohler SH, Honda GC Series consumer grade & GX Series commercial grade engines are 50 state approved
- ◆ LCT Maxx Series commercial grade 49 state approved engines – Not available in CA.
- Thermo-sensor (prevents overheating in bypass mode)
- All models meet or exceed PWMA standards of +/- 10%.