

**Steam / Hot / Cold Water Pressure Steamer – Natural Gas or LP Heated, Electric Motor**

The **HN Series** is a heavy-duty stationary unit offering high output and instant cleaning power with adjustable temperature for various cleaning applications. The powder coated frame and stainless steel front panels and coil enclosure offer aesthetics and a balance of protection and accessibility to components. High torque / low RPM belt driven pump ensures years of worry free service with built in overheat protection if machine is left on. The automatic electronic ignition eliminates the need to manually light a pilot and increases the safety of the machine.

<b>PRESSURE</b>	3500 psi
<b>FLOW CAPACITY</b>	4.3 gpm
<b>OUTLET TEMP</b>	Adjustable to 250°F (130°F rise)
<b>POWER/ENGINE</b>	10 hp
<b>VOLTS/PHASE/AMPS</b>	<b>E3C</b> is dual rated 208v or 230v - 3 ph, 29a <b>E4C</b> is 460v – 3ph, 13 amp
<b>CONTROLS/SWITCHES</b>	Lighted rocker switches, panel mounted soap control, adjustable thermostat
<b>PUMP</b>	CAT Pump, triplex ceramic plunger
<b>POWER DRIVE</b>	V-Belt drive with EZ Align™ pump rail
<b>PRES. CONTROL</b>	By-Pass-Cool™ system / Safety relief valve and burst disc
<b>WATER SUPPLY</b>	4 gallon float tank with double filtration and back flow prevention
<b>PRESSURE HOSE</b>	3/8 x 50' steel wire braided / 250°F 4000 psi rated
<b>GUN / WAND</b>	48" molded insulator wand, with quick coupler
<b>SOAP INJECTION</b>	Full pressure chemical injection, precision stainless steel metering valve
<b>NOZZLE</b>	#4.5 (15°, 40°), #3.5 (25° Steam)
<b>BURNER COIL</b>	Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 6 spiral, ceramic insulation
<b>BURNER/POWER</b>	Natural gas with auto ignition and 90 second safety lockout, cast iron ring, brass jets
<b>BURNER INPUT</b>	440,000 BTU (draft diverter recommended for optimal heating results)
<b>CONSTRUCTION</b>	Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap (stainless steel frame option available)
<b>WEIGHT/DIM</b>	490#, 48"l x 21"w x 49"h

\*Specifications subject to change without notification and may vary due to ambient conditions.

Not suitable for outdoor installation without protection from wind, overspray, rain, freezing

**Featuring:**

- ✓ **Open design** gives you full access to components
- ✓ **Adjustable Thermostat** with steam setting for various cleaning applications
- ✓ **By-Pass-Cool** system protects pump from overheating if left on after use
- ✓ **24 Volt Automatic Ignition** system on low emission natural gas burner

**Options...**

Hose reel (AR425, AR188) Draft diverter (BGD10), Downstream soap option (AC340), Multiple wash station shut-off (ACW20), Wind-up timer remote (AEN80), Full function remote (AENxx), Hour meter (AM603), Stainless frame upgrade (HS222), additional stainless panels-back and top (HS223)

Liquid Propane conversion (-LP)

Diesel fired conversion, includes 18g fuel tank (-D)

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

**DISTRIBUTED BY:** R.J. SAYERS DISTRIBUTING, LLC  
21020 CAMBODIA AVE  
FARMINGTON, MN 55024

