

Distributed By: R.J. Sayers Distributing, LLC 21020 Cambodia Ave Farmington, MN 55024 651-460-6101 / 800-456-9840 info@sayerswashsystems.com

> *Picture shown may not represent exact model. onsult factory.

4012-10KG 4GPM@4000PSI



TX1508G8 Pump GENERAL PUMP

Standard Accessories

- Gun/wand assembly with insulated grip ٠ and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20% chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

Standard Options

- ATK005 Adjustable Thermostat
- BRK100 Brake Kit
- **HRK415** Hose Reel Kit, 150' x 3/8" max. w/no add'l hose
- MC-B135 Machine Cover Blue Poly Marine Fabric

NOTE: AR, CAT, and VIPER gear drive pumps available - consult factory.

Standard Features

Rugged powder coated steel roll cage frame w/ lifting hook & 13 " flat-free tires & threaded axles

KOHLER CH440 Engine

- 4-wheel dimensions: 39 " L x 31 " W x 49 "
- Super efficient schedule 80 coil w/ onepiece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade engines
- **Reliable Beckett burners**
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents over heating in bypass mode)

NOTE: Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box. Subaru models are manual recoil start.