

# DEALER HOT WATER PRESSURE WASHERS

## Portable Electric Belt Drive | DHS Series

*The DHS Series of belt driven hot water pressure washers are ideal for cleaning applications requiring 20 or more hours of use a week. Recommended for heavy, consistent cleaning applications, this model is great for industrial and commercial jobs where you need to tackle nasty grime, oil and dirt.*



### Pump

- Belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector

### Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord

### Components

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)

### Frame

- Reinforced powder coated steel tube frame with center balanced lift
- 13-inch flat-free tires

### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

### Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/4-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off



# DEALER HOT WATER PRESSURE WASHERS

## Portable Electric Belt Drive | DHS Series



Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DH-2504-SE0E2G	2500	3.2	6.0 HP, 230V, 1Ø, 25.0A	General	NEMA 6-30P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	699 lb.	569 lb.
DH-2504-SE0E3G	2500	3.2	6.0 HP, 230V, 3Ø, 16.0A	General	NEMA L15-20P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	688 lb.	558 lb.
DH-3004-SE0E2G	3000	3.5	8.0 HP, 230V, 1Ø, 36.0A	General	NEMA 6-50P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	737 lb.	607 lb.
DH-3004-SE0E3G	3000	3.5	8.0 HP, 230V, 3Ø, 24.0A	General	NEMA L15-30P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	732 lb.	602 lb.
DH-3504-SE0E2G	3500	3.3	10.0 HP, 230V, 1Ø, 39.0A	General	NEMA 6-50P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	761 lb.	631 lb.
DH-3504-SE0E3G	3500	3.3	10.0 HP, 230V, 3Ø, 28.0A	General	NEMA L15-30P	10.0 gallons	2.10 gph	294,000	49.5x28x40.5in.	742 lb.	612 lb.

### Options:

Part Number	Description	Fits Models
HX-0070	<b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	2500 to 3500-PSI models
HX-0071	<b>Auto start/stop - steam</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	2500-PSI models
HX-0072	<b>Auto start/stop - steam</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	3000-PSI models
HX-0073	<b>Auto start/stop - steam</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	3500-PSI models
HX-0074	<b>Auto start/stop - CAD cell</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; monitors burner for proper ignition	2500 to 3500-PSI models
HX-0075	<b>Auto start/stop - steam - CAD cell</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F; monitors burner for proper ignition	2500-PSI models
HX-0076	<b>Auto start/stop - steam - CAD cell</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F; monitors burner for proper ignition	3000-PSI models
HX-0077	<b>Auto start/stop - steam - CAD cell</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart; reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F; monitors burner for proper ignition	3500-PSI models
HX-0085	<b>460V on 6.0-HP, 3-phase model</b> - Upgrades 230V, 3-phase model to operate at 460V, 3-phase, 18.0A	DH-2504-SE0E3G
HX-0086	<b>460V on 8.0-HP, 3-phase model</b> - Upgrades 230V, 3-phase model to operate at 460V, 3-phase, 12.0A	DH-3004-SE0E3G
HX-0087	<b>460V on 10.0-HP, 3-phase model</b> - Upgrades 230V, 3-phase model to operate at 460V, 3-phase, 14.0A	DH-3504-SE0E3G
HX-0088	<b>Skid feet</b> - Stationary applications	2500 to 3500-PSI models
HX-0161	<b>Hour meter</b> - Displays the number of hours unit has been in operation	2500 to 3500-PSI models

### Accessory:

Part Number	Description	Fits Models
850-0433	<b>50-ft. x 3/8-inch high pressure hose</b> - For when you need extra hose for added mobility	All models



NEMA 6-30P,  
30-amp plug



NEMA 6-50P,  
50-amp plug



NEMA L15-20P,  
20-amp plug



NEMA L15-30P,  
30-amp plug

Distributed By: **R.J. Sayers Distributing, LLC**  
**21020 Cambodia Ave**  
**Farmington, MN 55024**  
**800-456-9840 / 651-460-6101**  
**www.sayerswashsystems.com**  
**info@sayerswashsystems.com**

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).