

### ProTowWash® – Transport Trailer with 200 Gallon Tank

The T200 single axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The 200 Gallon water tank provides ample water to sustain many remote-cleaning requirements. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service are engineered into the T200 Series Pro Tow Wash.

TECHNICAL DATA	T200N	T200E
MACHINE CAPACITY	To be ordered with a hot water skid (up to 1100# total)	
SUSPENSION / AXLE	Single 3700# Torsion Axle-Up to 300% more wheel travel over conventional trailer	
TRAILER BRAKES	None	Electric Brake, Breakaway Switch***
WHEEL / TIRE	2 - 14" Spoke Rim, 5 Lug / ST205/75D 14 Tires, 1760 Pounds capacity per tire	
COUPLER / TONGUE	2" Ball Coupler, Dual Safety Chains	
VEHICLE HITCH/GVWR	2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 3500# GVWR – requires 2", class III ball on tow vehicle	
FENDERS	12 GA steel fender with recessed tail light mount and license plate light	
LIGHTS	Recessed Rubber Grommet Snap-In, DOT Approved	
WIRING	4 way flat electrical connector	7 way molded electrical connector
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	200 Gallon Capacity, Polyethylene, 10" lid, Garden Hose Fill Fitting	
TANK DRAW/FILTER	1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve	
FRAME CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
WEIGHT / DIMENSIONS	496 Lbs. Empty (No Machine) 125" x 70" x 61"	

\*Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped To Distributors Only – Not Available to Drop Ship – Assembly Required

\*\*\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery. Fenders and tires require installation if being shipped.

#### Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitation & contamination

#### Options...

Hose Reels, Lunette eye hitch, Stainless advertising panels, Chrome wheel upgrade, Custom trailer color (CTRLR), Front Bucket Rack (ACR02), 3-way ball valve (AW006), Light Bar rack (HLB98), High water tank shutoff (VVF18), Low water shutdown (AW410)-installed, Sand hopper, Hydro Vacuum wastewater recycle (AZV), 12v Chemical sprayer with 40g tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included  
 Shown with optional Hose Reel and Light Bar

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: **R.J. SAYERS DISTRIBUTING, LLC**  
 21020 CAMBODIA AVE  
 FARMINGTON, MN 55024

800-456-9840 / 651-460-6101 / info@sayerswashsystems.com

\* **WARNING:** Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.