

HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374
 phone 800.274.9376 or 1.909.799.9222
 www.hydrotek.us fax 909.799.9888

HD20004E2G

HD Series – Pressure Steamer

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HD Series** offers rugged, dependable, affordable washing. It features a heavy-duty stainless steel frame, handles, panels and coil protection – offering superior corrosion resistance, as well as four pneumatic wheels. Panel mounted temperature control offers the benefits of high pressure cleaning with water temperature from cold through full Steam Settings. Panel mounted controls allow the operator to vary the mixture of soap, or other additives, which can be delivered at full pressure – for optimal cleaning effectiveness. High efficiency coil and large capacity diesel fuel tank offer up to 8 hours of operation between refueling. Ideal for farm and agricultural applications, auto repair shops, and wherever sanitizing and degreasing are needed.

| | |
|--------------------------|------------------------------------------------------------------------------------------------|
| PRESSURE | 2000psi |
| FLOW CAPACITY | 3.8gpm |
| OUTLET TEMP | Adj. to 250°F (130°F Rise) |
| POWER/ENGINE | 5.0 HP |
| VOLTS/PHASE/AMPS | Dual rated for 208v or 230v - 1ph, 24a |
| POWER CORD | 35' cord with Ground Fault Circuit Interrupter for additional safety |
| CONTROLS/SWITCHES | Lighted rocker switches, panel mounted soap control, adjustable thermostat |
| PUMP | General Pump, Forged brass manifold, Triplex Ceramic Plunger |
| POWER DRIVE | V-Belt Drive with EZ Align™ pump rail, Low RPM – Cooler, Quieter |
| PRESSURE CONTROL | Adjustable Pressure Unloader, Safety Relief Valve, Burst Disc, By-Pass-Cool System |
| WATER SUPPLY | 4 Gal Float Tank, Double Inlet Filtration |
| PRESSURE HOSE | 3/8" x 50' Steel Wire Braid Hose, 3000 PSI, 250°F Rated |
| GUN / WAND | Insulated Shut Off Gun / 36" Wand w/Nozzle Quick Connector |
| SOAP INJECTION | Inlet soap/chemical injection, Injects Soap At Full Pressure |
| NOZZLE | #5.0(15°,40°) #4.0(25°) |
| BURNER COIL | Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation |
| BURNER/POWER | Beckett Oil Fired, Automatic Ignition, Forced Draft, Fuel Filter w/ Water Separator |
| BURNER FUEL / CAP | Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gal. capacity – 392,000 Btu input |
| CONSTRUCTION | All Stainless: frame, panels, coil wrap, and double wall coil end caps |
| WHEELS | 4) wheels installed |
| NET WEIGHT / DIMS | 381# 47x29x36 |

*Specifications subject to change without notification and may vary due to ambient conditions.



Featuring:

- ✓ **Efficient Heating:** Schedule 80 coil is stainless steel wrapped and insulated to make efficient use of the burner heat.
- ✓ **Flexible, Effective Cleaning:** Adjustable temperature with steam setting and soap/chemical injection delivers more cleaning power over a wide range of applications.
- ✓ **Compact and Portable:** Wheels included. Easily moved to wherever you need to clean

Options...

Stainless Steel Hose Reel (AR004)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: R.J. SAYERS DISTRIBUTING, LLC

21020 CAMBODIA AVE
 FARMINGTON, MN 55024
 800-456-9840 / 651-460-6101

Email: info@sayerswashsystems.com

Website: www.sayerswashsystems.com

