## HP PRESSURE STEAMERS

HP SERIES: DIESEL HEATED, ELECTRIC MOTOR









**EXCEPTIONAL HEAT OUTPUT FOR STUBBORN GRIME** 

# THYDRO TEK

## PRESSURE STEAMER

### HOT/COLD/STEAM - PORTABLE, ELECTRIC POWERED, DIESEL HEATED



#### ■ High Heat / High Flow System:

The balance of heat and flow increases your cleaning power providing a consistent superior performance. Auto ignition for peace of mind & ease of operation. High capacity diesel burner with higher temperature rise for faster cleaning.

#### SpiraLast™ Coil:

The coil is a Hydro Tek manufactured SpiraLast™ heating coil. Robotically fused ½" schedule 80 steel pipe is cold rolled to protect the steel pipe from fatigue and the spiral coil is then surrounded by ceramic insulation and stainless enclosure with double-wall end caps. Ask your dealer about the Lifetime Coil Warranty.

#### Auto Start and Time Delay Shutdown:

Operator has total control over the system from the trigger gun. This added convenience not only saves time and effort, it reduces wear and overheating of the pump and produces an energy efficient system that outperforms the traditional manual on/off.

#### Stainless Steel Coil Housing, Frame and Panels:

Rust-proof durable panels offer corrosion resistance and protection of your valuable investment from the harshest environments. Keeps your machine looking like new for years to come. Screw connects provide easy removal for <u>full</u> access to all major components and the Ultimate in serviceability.

#### **Adjustable Temperature with Steam Setting:**

Front mounted controls allows quick and easy adjustments of temperature and steam settings with higher heat than comparable washers for your toughest cleaning applications.

#### **NEMA4 - Water Tight Control Panel:**

ETL certified to UL1776 Class 2, for use in wash-down area, exceeding Industry standards. Special Hydro Tek control box features easy to use controls and provides instant access to electronics. **Dual voltage switch** on most 230v models allows you to simply flip a switch to change to 208v power supply.

#### CAT Belt Driven Pump:

Belt drive pump with low RPM drive - cooler, quieter, continuous duty performance. These Industrial triplex pumps outperform the competition in longevity - featuring concentrically bored & polished, graphite impregnated ceramic plungers with advanced seal design.

#### Diesel Fuel Tank with filtration:

Heavy Duty "roto-molded" rust free fuel tank with water separating fuel filter to protect against contaminated fuel. Extended run time (up to 5 hrs) eliminates interruptions.

#### Chemical Injection:

Equipped with inlet soap injection combined with precision chemical metering valve and float tank to inject soap at full pressure for optimal cleaning effectiveness. Panel mounted controls enable the operator to vary the mixture of soap or other additives with ease.

#### Portability:

HP Series comes standard with four large tires mounted on stainless axles and two lift handles.

#### More Standard Features...

- Heavy duty industrial motor with thermal overload protection
- Burst disc technology for operator safety
- Insulated quick connect nozzles
- 50' of heavy duty high pressure hose
- Stainless adjustable pressure wand and heavy duty trigger gun
- Panel mounted hour meter

**Unmatched Durability:** The HP is a proven model manufactured and refined for over two decades.

## HYDROTEK CLEANING EQUIPMENT MEG.

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888









| Specifications   |      |     |        |     |                |
|--|------|-----|--------|-----|----------------|
| Model  | PSI  | GPM | Temp.  | HP  | Voltage        |
| HP20005E8  | 2000 | 4.3 | 250° F | 6.5 | 208/230v - 1ph |
| HP22005E2  | 2200 | 4.3 | 250° F | 6.5 | 230v - 1ph     |
| HP30004E2 *  | 3000 | 3.9 | 250° F | 8   | 208/230v - 1ph |
| HP35005E3  | 3500 | 4.3 | 250° F | 10  | 208/230v - 3ph |
| HP35005E4  | 3500 | 4.3 | 250° F | 10  | 460v - 3ph     |
| Specifications may vary, consult factory for custom models |      |     |        |     |                |

\*HP30004E2 is not ETL Listed / UL1776 Certified, requires additional options

**Dimensions:** 46" x 29" x 39"

#### Optional Accessories...

Hose and wand extension, Stainless hose reel



#### **DISTRIBUTED BY:**

R.J. SAYERS DISTRIBUTING, LLC 21020 CAMBODIA AVE FARMINGTON, MN 55024 800-456-9840 / 651-460-6101

Email: info@sayerswashsystems.com Website: www.sayerswashsystems.com