

#### Pump.

Equipped with the Mi-T-M Pressure Relief Start which eliminates pressure build-up in the system | Thermal relief valve | In-line water strainer | Built-in low pressure detergent injector

### Frame:

Powder coated steel frame and base plate with  $1\frac{1}{4}$ -inch tube handles 10-inch flat-free tires

#### Unit Includes:

Quick connect nozzles - 15°, 25° and detergent nozzle | 25-foot x %-inch wire-braided high pressure hose (50-foot on CM-3600 and CM-4200 models) | Professional-grade trigger gun | Two-piece, 36-inch lance

## Limited Warranties:

1 year AR and Mi-T-M pumps | 1 year Mi-T-M engine

USAGE	Residential/Commercial	Commercial	Commercial	Commercial
MODEL NO.	CM-3000-0MMB	CM-3200-0MMB (pictured)	CM-3600-0MMB	CM-4200-0MMB
PSI	3000	3200	3600	4200
GPM	2.4	2.4	2.8	3.4
DISPLACEMENT/ENGINE	212cc Mi-T-M OHV	212cc Mi-T-M OHV	300cc Mi-T-M OHV	420cc Mi-T-M OHV
PUMP	Mi-T-M, axial	Mi-T-M, crankshaft	AR, crankshaft	AR, crankshaft
UNLOADER	Fixed pressure	Adjustable pressure	Adjustable pressure	Adjustable pressure
DIMENSIONS (LxWxH)	37x21x24.5in.	37x21x24.5in.	40x22.5x24.5in.	40x22.5x24.5in.
SHIP WT.	100 lb.	110 lb.	180 lb.	192 lb.
NET WT.	75 lb.	85 lb.	130 lb.	142 lb.

# Consult factory for more information on these available options: