

HOT WATER MINI TRAILER

Portable Gasoline

Belt Drive | Trailer-Mount Pressure Washer



The compact design of the new Mi-T-M hot water mini trailer offers ease of transport without sacrificing powerful cleaning capabilities. This trailer package is engineered with a durable powder coated steel frame, a rear locking storage area and an industrial 4000 PSI belt-driven pressure washer with a 12V Beckett burner.



HMT-4004-0MGH shown with optional adjustable trailer coupler hitch, TX-0010

Pump

- Belt drive triplex piston General pump with ceramic plungers
- Adjustable stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve

Engine

- Performance proven Honda engine with low-oil protection
- Remote engine start and choke
- 12V electric start – battery not included

Frame

- Reinforced powder coated steel frame
- Locking rear storage area – 2.875 cubic feet
- Sealed LED trailer lights
- 2-inch ball hitch
- Caster brake (Use when unhitched)

Components

- 1/2-inch schedule 80 pipe coil with 4-pancake heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Engine and burner hour meters

Miscellaneous

- Temperature rise 140°F/60°C above ambient

Safety Features

- Removable safety flag for transportation and guidance when backing up
- Recommended maximum speed is 65 mph
- DOT approved and National Association of Trailer Manufacturers (NATM) certified trailer
- 250°F high temperature safety limit switch

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

POWERED by
HONDA



HOT WATER MINI TRAILER

Portable Gasoline

Belt Drive | Trailer-Mount Pressure Washer



Model Number	PSI	GPM	Displacement/Engine	Pump	Engine Fuel Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Axle	Tires	Dimensions (LxWxH)	Gross Vehicle Wt.
HMT-4004-OMGH	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.45 gph	343,000	1,000 lb.	(2) 4.80-8 8in. bias ply	99x43.5x36in.	1,000 lb.

Options:		
Part Number	Description	Fits Model
TX-0010	Adjustable trailer coupler hitch - Heavy-duty, 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket with visual indication of proper closure around the ball - all to ensure a quick, easy and secure hook-up	HMT-4004-OMGH
TX-0020	High pressure hose reel - 12-inch hose reel, 100-foot maximum hose length	HMT-4004-OMGH

Accessories:		
Part Number	Description	Fits Model
15-0160	75-foot x 3/8-inch hose - 4500-PSI rated, R2, for use with hose reel, TX-0020	HMT-4004-OMGH
15-0161	100-foot x 3/8-inch hose - 4500-PSI rated, R2, for use with hose reel, TX-0020	HMT-4004-OMGH
20-1366A52	Black powder coated rain cap - Protects boiler from moisture build-up when unit is left outside, octagonal	HMT-4004-OMGH
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	HMT-4004-OMGH



HMT-4004-OMGH rear storage area

! WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.