

# HYDRO TEK

CLEANING EQUIPMENT MFG.

2353 Almond Ave. Redlands, CA 92374  
 phone 800.274.9376 or 1.909.799.9222  
 www.hydrotek.us fax 909.799.9888

# SS35004VG

## SS Series – Mobile Wash Skid

### Steam / Hot / Cold Water – Self Contained: Diesel Heated, Gas Engine, 12v Burner

The **SS Series** is a power washer that uses the 12-volt charging system on the engine to power the diesel-fired burner giving you continuous hot water. Its compact size allows passage through commercial doorways, and simple design makes it easy to run and maintain. The SS series is versatile, you select a mounting option: on a trailer, on a truck, on wheels or stationary. The SS Series has the output to perform heavy duty cleaning without needing any outside electrical power. Simply turn the key for high pressure, hot cleaning strength. An invaluable piece of equipment for property management companies, farmers, mechanics or anyone requiring a mobile cleaning solution for dirt, grease, and grime.

<b>PRESSURE</b>	3500 psi
<b>FLOW CAPACITY</b>	4 gpm
<b>OUTLET TEMP</b>	Adjustable to 250°F (140°F rise)
<b>POWER/ENGINE</b>	479cc Vanguard, twin cylinder, Electric key start
<b>ENGINE FUEL/CAP</b>	Unleaded, 8 gal
<b>CONTROLS/SWITCHES</b>	Adjustable thermostat, lighted control switch
<b>PUMP</b>	General Pump, Triplex Ceramic Plunger
<b>POWER DRIVE</b>	V-Belt Drive with EZ Align™ pump rail, stainless belt guard
<b>PRESSURE CONTROL</b>	Unloader valve, Industrial fittings, Safety burst disc, Pressure relief valve
<b>WATER SUPPLY</b>	Pressure feed from garden hose with convenient frame mounted fitting, (float tank avail.)
<b>PRESSURE HOSE</b>	3/8" x 50', 4000psi
<b>GUN/WAND</b>	48" molded insulator wand with multi-nozzle holder and quick coupler
<b>SOAP INJECTION</b>	Optional soap injection available
<b>NOZZLE</b>	Size 4.0 (15°,40°) and 3.5 (25° steam)
<b>BURNER COIL</b>	Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
<b>BURNER/POWER</b>	Oil fired, 12V, 20amp fuse protected, auto ignition, in-line fuel filter, flow switch burner control
<b>BURNER FUEL/CAP</b>	Diesel fuel, kerosene, or fuel oil, 8 gallons – 390,600 Btu input
<b>CONSTRUCTION</b>	Rugged, powder coated Pro-Tect-It™ frame, stainless panels, coil wrap, and double-wall coil end caps
<b>WHEELS</b>	Optional wheel kit available
<b>WEIGHT/DIMENSION</b>	476#, 47 1/2" l x 27.5" w x 40.25" h

Specifications subject to change without notification and may vary due to ambient conditions – Battery not included

#### Featuring:

- ✓ **Rugged "Pro-Tec-It" Frame** surrounds and protects vital pressure washer components
- ✓ **Stainless Steel** panels for Lifetime Corrosion Resistance
- ✓ **EZ Align™**: Hydro Tek's belt tensioning system makes belt adjustments easy, with a single bolt, and has an integrated self-aligning mono rail pump mount
- ✓ **High Altitude Rated** – extra air band capacity available
- ✓ **Low Pressure, Hot (160°+) water rinse**

#### Options...

Hose Reel (AR188), Hour meter (AM305), Wheel Kit options (AHA12, AHB12, or AHS12), Downstream soap injection kit (AC340), Float tank with inlet injection (WT0SS), Antifreeze tank (WT0SW), Custom skid color (CTSKD), Mobile Wash Trailer, Tank Skid



TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

**DISTRIBUTED BY:** R.J. SAYERS DISTRIBUTING, LLC  
 21020 CAMBODIA AVE  
 FARMINGTON, MN 55024

©2012 Hydro Tek (rev05/15 SS35004VG)

800-456-9840 / 651-460-6101 / Email: info@sayerswashsystems.com / Website: www.sayerswashsystems.com