DEALER COLD WATER PRESSURE WASHERS Premium Series Electric | Portable | Belt Drive

Perfect for cleaning heavily soiled equipment located inside commercial facilities, use this unit to clean grimy floors and concrete walls of garages and service shops. It's a great tool to keep indoor pools free from dirt, mold and mildew.



Pump

- Belt drive triplex piston General pump with ceramic plungers
- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold

- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Frame

- Powder coated steel frame and base plate with 11/4-inch tube handles
- 13-inch flat-free tires
- Enclosed belt guard

Motor

- Totally enclosed fan-cooled electric motor with thermal overload protection

DC-4004-W1E3G shown with 460V, 3-phase motor option, CX-0057

- 10-foot power cord

Component

- Heavy-duty dual cogged belt drive system

Unit Includes:

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x 3//- inch non-marking high pressure hose

4000 PS

- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 4000 and 5000-PSI models)



DEALER COLD WATER PRESSURE WASHERS Premium Series Electric | Portable | Belt Drive



Model Number	PSI	GPM	Horsepower/Motor	Pump	Unloader	Plug Type	Lance	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DC-2405-W4E2G	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	General	Factory preset	NEMA 6-50P	36in.	46x28x30in.	345 lb.	333 lb.
DC-2405-W4E3G*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	Factory preset	NEMA L15-30P	36in.	45.5x32.5x30in.	355 lb.	343 lb.
DC-3004-W4E2G	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	General	Factory preset	NEMA 6-50P	36in.	46x28x30in.	350 lb.	338 lb.
DC-3004-W4E3G*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	Factory preset	NEMA L15-30P	36in.	45.5x32.5x30in.	403 lb.	301 lb.
DC-3005-W0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	Factory preset	NEMA 6-50P	36in.	45.5x32.5x30in.	470 lb.	396 lb.
DC-3005-W0E3G*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	Factory preset	NEMA 15-50P	36in.	45.5x32.5x30in.	450 lb.	376 lb.
DC-4004-W1E3G	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	Factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.
DC-5004-W0E3G*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	Factory preset	NEMA 15-50P	48in.	45.5x32.5x30in.	505 lb.	431 lb.

*460V motors available as options.

Description	
Description	Fits Models
460V on 8.0-HP, 3-phase models - For when you have 460V of power available	DC-2405-W4E3G & DC-3004-W4E3G
36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having	DC-2405, DC-3004 &
to change tips	DC-3005-PSI models
460V on 15.0-HP, 3-phase models - For when you have 460V of power available	DC-4004-W1E3G & DC-5004-W0E3G
460V on 10.0-HP, 3-phase model - For when you have 460V of power available	DC-3005-W0E3G
Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for	DC-2405 & DC-3004 models
stationary applications	
Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for	DC-3005, DC-4004 &
stationary applications	DC-5004 models
	36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips 460V on 15.0-HP, 3-phase models - For when you have 460V of power available 460V on 10.0-HP, 3-phase model - For when you have 460V of power available Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for

Accessories:							
Part Number	Description	Fits Models					
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models					
851-0317	50-ft. x %-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-5004-W0E3G					
851-0338	50-ft. x %-in. non-marking high pressure hose - For when you need extra hose for added mobility	2400 to 4000-PSI models					
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models					





NEMA 15-50P,

50-amp plug



NEMA L15-30P, 30-amp plug

NEMA 6-50P, 50-amp plug

Distributed By: R.J. Sayers Distributing, LLC 21020 Cambodia Ave Farmington, MN 55024 800-456-9840 / 651-460-6101 www.sayerswashsystems.com info@sayerswashsystems.com

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.